



CONCRETE PLACING

FLEXSHAFT CONCRETE VIBRATOR

- Heat treated nose cap and rotor to reduce wear and tear from abrasive concrete aggregates.
- Heavy rotor for high vibration amplitude gets the job done faster.
- Rubber support sleeve and vibration counter spring reduces vibration transfer to the operator – improved safety and comfort.
- Two sealed bearings isolate load transfer resulting in improved durability.
- Double oil seal protection and heavy duty double row self-aligning bearing extend service life.



Steel Tip



Rubber Tip

1300 353 986
www.flextool.com.au



FLEXSHAFT CONCRETE VIBRATOR

Australia's original VP series of immersion Concrete Vibrators produce high frequency vibration allowing for the efficient compaction of all types of concrete mixes. The epicyclic design of the of the VP series is supported by three heavy duty bearings and double oil seal protection for optimum performance and longer service life.

Product & Performance Specifications							
Flexshaft Concrete Vibrators							
Model Number	FVP30-6	FVP40-6	FVP40-9	FVP50-6	FVP50-9	FVP60-6	FVP60-9
Nose Cap Type	Steel						
Vibrator Head Dia (mm)	28	38		50		60	
Flexshaft Length (m)	6	6	9	6	9	6	9
Operating Weight (kg)	14	19	26	22	28	23	29
Shaft Inner Core Dia (mm)	8	12					
Shaft Casing Dia (mm)	28	32					
Frequency (vib/min)	12600	12300	12300	12000	12000	12000	12000
Frequency (Hz)	210	205	205	200	200	200	200
Amplitude in Air (mm)	1.4	1.7	1.7	2.2	2.2	2.4	2.4
Product Code	FT201794-UNIT	FT201795-UNIT	FT201793-UNIT	FT201796-UNIT	FT201792-UNIT	FT201797-UNIT	FT201791-UNIT
Barcode	9300611599001	9300611599049	9300611598233	9300611599056	9300611598240	9300611599063	9300611598264

Product & Performance Specifications				
Flexshaft Concrete Vibrators				
Model Number	FVP40R-6	FVP50R-6	FVP60R-6	FVP60R-9
Nose Cap Type	Rubber			
Vibrator Head Dia (mm)	38	50	60	
Flexshaft Length (m)	6	6	6	9
Operating Weight (kg)	19	21.5	22.5	29
Shaft Inner Core Dia (mm)	12			
Shaft Casing Dia (mm)	32			
Frequency (vib/min)	12300	12000	12000	12000
Frequency (Hz)	205	200	200	200
Amplitude in Air (mm)	1.7	2.2	2.4	2.4
Product Code	FT201787-UNIT	FT201788-UNIT	FT201789-UNIT	FT201790-UNIT
Barcode	9300611599018	9300611599025	9300611599032	9300611598257



1300 353 986
www.flextool.com.au



Parchem Construction Supplies Pty Ltd
7 Lucca Road, Wyong NSW AUS 2259